




1		2		3		4		5		Customer drawing	
REV	ECN NO	DESCRIPTION			DATE	APPROVED					
AA	-	NEW RELEASED			2015. 09. 11	CLARA					







Electrical specifications:
 Use of voltage range: 30V
 Current range: 0.5A
 Temperature range: -20°C~+80°C

Material specifications
 Connector: Type-C Standard
 Overmolding: Black PVC

Electrical testing of finished cable
 100% Open / Short / Miswiring testing
 Insulation resistance: DC150V 10MΩMin
 Conductor resistance: 3Ω Max

Manufacturer: Bomcan



 <div style="display: inline-block; vertical-align: middle;"> This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com </div>							
DESCRIPTION		STANDARD TYPE-C PLUG/TYPE-C SOCKET ADAPTER					
DWG NO	TYPE-C ADAPTER	BOMCAN PART No		USB-CPCS-ADAPTER			
DRAWN BY	CLARA 2015. 09. 11	CUSTOMER P/N		-			
CHECKED BY	CALEB 2015. 09. 11	SIZE: A4	SHEET	UNIT	SCALE	Third angle projection	
APPROVED BY	BILL 2015. 09. 11	REV: AA	1 of 1	MM	FREE	